



**Safety Data Sheet**  
**Drain Clean/ Auto Glass Washer Super Concentrate/ Oven**  
**Grease Dissolver/ Heavy Duty Oven and Grill Revision 3,**  
**22/08/2024**

## 1. IDENTIFICATION

<b>Product Name</b>	<b>Drain clean/ Auto Glass Washer Super Concentrate/ Oven Grease Dissolver/</b>
<b>Other Names</b>	<b>Heavy duty oven and grill</b>
<b>Uses</b>	KOH Liquid
<b>Chemical Family</b>	Cleaning solution for use with commercial machines.
<b>Chemical Formula</b>	KOH
<b>Chemical Name</b>	Potassium hydroxide solution
<b>Product Description</b>	No Data Available

### Contact Details of the Supplier of this Safety Data Sheet

<b>Organisation</b>	<b>Location</b>	<b>Telephone</b>
Aurora Cleaning Supplies	F1 / 5 Bungaleen Court Dandenong South VIC 3175	03 9768 2669

### Emergency Contact Details

*For emergencies only; DO NOT contact these companies for general product advice.*

<b>Organisation</b>	<b>Location</b>	<b>Telephone</b>
Chemcall	Australia	1800-127406 +64-4-9179888
Chemcall	Malaysia	+64-4-9179888
Chemcall	New Zealand	0800-243622 +64-4-9179888
National Poisons Centre	New Zealand	0800-764766
CHEMTREC	USA & Canada	1-800-424-9300 CN723420 +1-703-527-3887

## 2. HAZARD IDENTIFICATION

**Poisons Schedule (Aust)**                      Schedule 6

**Globally Harmonised System**

<b>Hazard Classification</b>	Hazardous according to the criteria of the Globally Harmonised System of Classification and Labelling of Chemicals (GHS)
<b>Hazard Categories</b>	Corrosive to Metals - Category 1 Acute Toxicity (Oral) - Category 4 Skin Corrosion/Irritation - Category 1A Serious Eye Damage/Irritation - Category 1

**Pictograms****Signal Word**

Danger

**Hazard Statements**

<b>H290</b>	May be corrosive to metals.
<b>H302</b>	Harmful if swallowed.
<b>H314</b>	Causes severe skin burns and eye damage.

**Precautionary Statements**

Prevention

<b>P270</b>	Do not eat, drink or smoke when using this product.
<b>P280</b>	Wear protective gloves/protective clothing/eye protection/face protection.
<b>P260</b>	Do not breathe gas/mist/vapours/spray.

Response

<b>P301 + P330 + P331</b>	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
<b>P303 + P361 + P353</b>	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
<b>P304 + P340</b>	IF INHALED: Remove victim to fresh air and keep comfortable for breathing.
<b>P305 + P351 + P338</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>P310</b>	Immediately call a POISON CENTER or doctor.
<b>P330</b>	Rinse mouth.
<b>P363</b>	Wash contaminated clothing before reuse.
<b>P390</b>	Absorb spillage to prevent material-damage.
Storage	<b>P405</b> Store locked up.
	<b>P406</b> Store in corrosive resistant container with a resistant inner liner.
Disposal	<b>P501</b> Dispose of contents/container in accordance with local / regional / national / international regulations.

**National Transport Commission (Australia)**

Australian Code for the Transport of Dangerous Goods by Road &amp; Rail (ADG Code)

**Dangerous Goods Classification**

Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road &amp; Rail (ADG Code)

**Environmental Protection Authority (New Zealand)**

Hazardous Substances and New Organisms Amendment Act 2015

**HSNO Classifications**Health  
Hazards

<b>6.1D</b>	Substances that are acutely toxic - Harmful
<b>8.1A</b>	Substances that are corrosive to metals
<b>8.2B</b>	Substances that are corrosive to dermal tissue UN PGII
<b>8.3A</b>	Substances that are corrosive to ocular tissue

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Ingredients

Chemical Entity	Formula	CAS Number	Proportion
Water	H <sub>2</sub> O	7732-18-5	48 - 80 %
Potassium hydroxide	KOH	1310-58-3	20 - 52 %

### 4. FIRST AID MEASURES

#### Description of necessary measures according to routes of exposure

<b>Swallowed</b>	IF SWALLOWED: Rinse mouth, then drink a glass of water. Do NOT induce vomiting. Immediately call a Poison Centre or doctor/physician for advice. Never give anything by mouth to an unconscious person.
<b>Eye</b>	IF IN EYES: Immediately flush eyes with running water for several minutes, holding eyelids open and occasionally lifting the upper and lower lids. Immediately call a Poison Centre or doctor/physician for advice. Remove contact lenses if present and easy to do. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. *Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
<b>Skin</b>	IF ON SKIN (or hair): Remove contaminated clothing and shoes immediately. Flush skin and hair with running water for at least 15 minutes. For minor skin contact, avoid spreading material on unaffected skin. In case of gross contamination, drench contaminated clothing and skin with plenty of water before removing clothes. Immediately call a Poison Centre or doctor/physician for advice. Wash contaminated clothing and shoes before reuse.
<b>Inhaled</b>	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a Poison Centre or doctor/physician for advice. Apply resuscitation if victim is not breathing - Do not use direct mouth-to-mouth method if victim ingested or inhaled the substance; use alternative respiratory method or proper respiratory device - Administer oxygen if breathing is difficult.
<b>Advice to Doctor</b>	Keep victim calm and warm - Obtain immediate medical care. Ensure that attending medical personnel are aware of the identity and nature of the product(s) involved, and take precautions to protect themselves.
<b>Medical Conditions Aggravated by Exposure</b>	No information available.

### 5. FIRE FIGHTING MEASURES

<b>General Measures</b>	If safe to do so, move undamaged containers from fire area. Cool containers with water spray until well after fire is out. Avoid getting water inside containers.
<b>Flammability Conditions</b>	Non-combustible; Material itself does not burn.
<b>Extinguishing Media</b>	If material is involved in a fire, dry chemical, Carbon dioxide (CO <sub>2</sub> ), foam or water spray for extinction.
<b>Fire and Explosion Hazard</b>	Containers may explode when heated. Contact with metals may evolve flammable hydrogen gas.
<b>Hazardous Products of Combustion</b>	Fire or heat will produce irritating, toxic and/or corrosive gases, including Potassium oxide.
<b>Special Fire Fighting Instructions</b>	Contain runoff from fire control or dilution water - Runoff may be toxic and/or corrosive and may pollute waterways.
<b>Personal Protective Equipment</b>	Wear self-contained breathing apparatus (SCBA) and chemical splash suit. Fully-encapsulating, gas-tight suits should be worn for maximum protection. Structural firefighter's uniform is NOT effective for this material.
<b>Flash Point</b>	No Data Available
<b>Lower Explosion Limit</b>	No Data Available
<b>Upper Explosion Limit</b>	No Data Available
<b>Auto Ignition Temperature</b>	No Data Available
<b>Hazchem Code</b>	2R

### 6. ACCIDENTAL RELEASE MEASURES

<b>General Response Procedure</b>	Ensure adequate ventilation - Ventilate enclosed spaces before entering. ELIMINATE all ignition sources. Do not touch or walk through spilled material. Do not breathe vapours and prevent contact with eyes, skin and clothing.
<b>Clean Up Procedures</b>	Absorb with earth, sand or other non-combustible material and transfer to a suitable container for disposal (see SECTION 13). For large amounts, pump-off recoverable product.
<b>Containment</b>	Stop leak if safe to do so - Prevent entry into waterways, drains or confined areas. Cover with plastic sheet to prevent spreading.
<b>Decontamination</b>	Neutralise residues with dilute acid. Wash area down with excess water.
<b>Environmental Precautionary Measures</b>	Spillages and decontamination runoff should be prevented from entering drains and watercourses.
<b>Evacuation Criteria</b>	Spill or leak area should be isolated immediately. Keep unauthorised personnel away. Keep upwind and to higher ground. Large spill: Immediately contact Police or Fire Brigade; Consider initial downwind evacuation of areas within at least 250 m.
<b>Personal Precautionary Measures</b>	Do not touch damaged containers or spilled material unless wearing appropriate protective clothing (see SECTION 8). Wear SCBA and chemical splash suit. Fully-encapsulating, gas-tight suits should be worn for maximum protection.

## 7. HANDLING AND STORAGE

<b>Handling</b>	Safety showers and eyewash facilities should be provided within the immediate work area for emergency use. Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Do not breathe mist/vapours/aerosols and prevent contact with eyes, skin and clothing. Do not ingest. Wear protective gloves/protective clothing/eye protection/face protection (see SECTION 8). Avoid contact with incompatible materials. Absorb spillage to prevent material damage (see SECTION 6).
<b>Storage</b>	Store in a cool, dry and well-ventilated place, out of direct sunlight. Prevent freezing during winter. Keep container tightly closed when not in use - check regularly for leaks. Protect from water/moisture. Keep away from heat and sources of ignition - No smoking. Keep away from foodstuffs and incompatible materials (see SECTION 10). Store locked up.
<b>Container</b>	Keep only in the original container or corrosive resistant container. Do not store in aluminium or galvanised containers nor use die-cast zinc or aluminium bungs; steel bungs should be used.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<b>General</b>	COMPONENT: Potassium hydroxide (CAS No. 1310-58-3): <ul style="list-style-type: none"><li>- Safe Work Australia Exposure Standard: TWA = 2 mg/m<sup>3</sup> Peak limitation.</li><li>- New Zealand Workplace Exposure Standard: TWA = 2 mg/m<sup>3</sup> Ceiling.</li><li>- NIOSH REL = 2 mg/m<sup>3</sup></li></ul>
<b>Exposure Limits</b>	No Data Available
<b>Biological Limits</b>	No information available.
<b>Engineering Measures</b>	A system of local and/or general exhaust is recommended to keep employee exposures as low as possible. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area.
<b>Personal Protection Equipment</b>	<ul style="list-style-type: none"><li>- Respiratory protection: Under conditions of frequent use or heavy exposure, respiratory protection may be needed. Recommended: Particulate/mist filter respirator (refer to AS/NZS 1715 &amp; 1716).</li><li>- Eye/face protection: Wear appropriate eye protection to prevent eye contact. Recommended: Chemical goggles (primary); Face shield (secondary).</li><li>- Hand protection: Wear protective gloves. Recommended: Long (elbow-length) impervious gloves.</li><li>- Skin/body protection: Wear appropriate personal protective clothing to prevent skin contact. Recommended: Overalls, splash apron or equivalent chemical impervious outer garment and rubber boots.</li></ul>
<b>Special Hazards Precautions</b>	No information available.
<b>Work Hygienic Practices</b>	Do not eat, drink or smoke when using this product. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical State</b>	Liquid
<b>Appearance</b>	Liquid
<b>Odour</b>	Odourless
<b>Colour</b>	Transparent/Opaque
<b>pH</b>	>=12
<b>Vapour Pressure</b>	2.5 mmHg (@ 20 °C)
<b>Relative Vapour Density</b>	0.62 Air = 1
<b>Boiling Point</b>	143 °C (50% soln.)
<b>Melting Point</b>	No Data Available
<b>Freezing Point</b>	4.4 °C
<b>Solubility</b>	Miscible with water
<b>Specific Gravity</b>	1.516
<b>Flash Point</b>	No Data Available
<b>Auto Ignition Temp</b>	No Data Available
<b>Evaporation Rate</b>	No Data Available
<b>Bulk Density</b>	No Data Available
<b>Corrosion Rate</b>	No Data Available
<b>Decomposition Temperature</b>	No Data Available
<b>Density</b>	No Data Available
<b>Specific Heat</b>	No Data Available
<b>Molecular Weight</b>	No Data Available
<b>Net Propellant Weight</b>	No Data Available
<b>Octanol Water Coefficient</b>	No Data Available
<b>Particle Size</b>	No Data Available
<b>Partition Coefficient</b>	No Data Available
<b>Saturated Vapour Concentration</b>	No Data Available
<b>Vapour Temperature</b>	No Data Available
<b>Viscosity</b>	6.0 cP (@ 15.6 °C)
<b>Volatile Percent</b>	No Data Available
<b>VOC Volume</b>	No Data Available
<b>Additional Characteristics</b>	No information available.
<b>Potential for Dust Explosion</b>	Not applicable.
<b>Fast or Intensely Burning Characteristics</b>	No information available.
<b>Flame Propagation or Burning Rate of Solid Materials</b>	No information available.
<b>Non-Flammables That Could Contribute Unusual Hazards to a Fire</b>	No information available.
<b>Properties That May Initiate or Contribute to Fire Intensity</b>	Non-combustible; Material itself does not burn.
<b>Reactions That Release Gases or Vapours</b>	Fire or heat will produce irritating, toxic and/or corrosive gases, including Potassium oxide.
<b>Release of Invisible Flammable Vapours and Gases</b>	Contact with metals may evolve flammable hydrogen gas.

## 10. STABILITY AND REACTIVITY

### General Information

Potassium hydroxide solution in water is a strong base; It reacts violently with acid and is corrosive to metals such as aluminium, tin, lead and zinc. Reacts with ammonium salts; This produces ammonia and generates fire hazard. Contact with moisture and water may generate sufficient heat to ignite combustible materials.

This material is stable under recommended storage conditions at normal temperature and pressure.

**Chemical Stability****Conditions to Avoid**

Keep away from heat and sources of ignition.

**Materials to Avoid**

Incompatible/reactive with acids, metals, halocarbon compounds, oxidisers, ammonium salts, reducing agents, combustible materials.

**Hazardous Decomposition Products**

Fire or heat will produce irritating, toxic and/or corrosive gases, including Potassium oxide. Contact with metals may evolve flammable hydrogen gas.

**Hazardous Polymerisation**

Hazardous polymerisation will not occur.

**11. TOXICOLOGICAL INFORMATION****General Information**

- Acute toxicity: Harmful if swallowed. Corrosive on ingestion; Symptoms include abdominal pain, burns in mouth and throat, burning sensation in the throat and chest, nausea, vomiting, shock or collapse.
- Skin corrosion/irritation: Causes severe skin burns. Potassium hydroxide is very corrosive to skin; It causes deep penetrating burns and necrosis.
- Eye damage/irritation: Causes serious eye damage. Potassium hydroxide is very corrosive to the eyes; Symptoms include redness, pain, blurred vision, severe burns.
- Respiratory/skin sensitisation: Potassium hydroxide is not considered to be a skin sensitiser.
- Germ cell mutagenicity: No information available.
- Carcinogenicity: No component in this material is listed as carcinogenic according to the International Agency for Research on Cancer (IARC).
- Reproductive toxicity: No information available.
- STOT (single exposure): Potassium hydroxide is very corrosive to the respiratory tract. Breathing in mists or aerosols may produce respiratory irritation. Symptoms include cough, sore throat, burning sensation, shortness of breath.
- STOT (repeated exposure): Repeated or prolonged contact with skin may cause dermatitis.
- Aspiration toxicity: No information available.

**Acute****Ingestion**

Acute toxicity (Oral):  
COMPONENT: Potassium hydroxide (CAS No. 1310-58-3):  
- LD50, Rat: 333 mg/kg bw. [Supplier's SDS].

**Carcinogen Category**

None

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

Aquatic toxicity:  
- LC50, Fish (Gambusia affinis): 80 mg/L (96 h).  
- EC50, Crustacea (Daphnia magna): 660 mg/L (48 h).  
- EC50, Algae/aquatic plants (Nitscheria linearis): 1,337 mg/L (120 h).

**Persistence/Degradability**

Ready biodegradation.

**Mobility**

No information available.

**Environmental Fate**

Prevent entry into drains and waterways.

**Bioaccumulation Potential**

- BCF: 3.162  
- log Kow: -3.88

**Environmental Impact**

No Data Available

**13. DISPOSAL CONSIDERATIONS****General Information**

Dispose of contents/container in accordance with local/regional/national regulations.

**Special Precautions for Land Fill**

No information available.

**14. TRANSPORT INFORMATION**

Land Transport (Australia)

ADG Code

Proper Shipping Name	POTASSIUM HYDROXIDE SOLUTION
Class	8 Corrosive Substances
Subsidiary Risk(s)	No Data Available
EPG	37 Toxic And/Or Corrosive Substances Non-Combustible
UN Number	1814
Hazchem	2R
Pack Group	II
Special Provision	No Data Available

Land Transport (Malaysia)

ADR Code

Proper Shipping Name	POTASSIUM HYDROXIDE SOLUTION
Class	8 Corrosive Substances
Subsidiary Risk(s)	No Data Available
EPG	37 Toxic And/Or Corrosive Substances Non-Combustible
UN Number	1814
Hazchem	2R
Pack Group	II
Special Provision	No Data Available

Land Transport (New Zealand)

NZS5433

Proper Shipping Name	POTASSIUM HYDROXIDE SOLUTION
Class	8 Corrosive Substances
Subsidiary Risk(s)	No Data Available
EPG	37 Toxic And/Or Corrosive Substances Non-Combustible
UN Number	1814
Hazchem	2R
Pack Group	II
Special Provision	No Data Available

Land Transport (United States of America)

US DOT

Proper Shipping Name	POTASSIUM HYDROXIDE SOLUTION
Class	8 Corrosive Substances
Subsidiary Risk(s)	No Data Available
ERG	154 Substances - Toxic and/or Corrosive (Non-Combustible)
UN Number	1814
Hazchem	2R
Pack Group	II
Special Provision	No Data Available

Sea Transport

IMDG Code

Proper Shipping Name	POTASSIUM HYDROXIDE SOLUTION
Class	8 Corrosive Substances

Subsidiary Risk(s)	No Data Available
UN Number	1814
Hazchem	2R
Pack Group	II
Special Provision	No Data Available
EMS	F-A, S-B
Marine Pollutant	No

#### Air Transport

IATA DGR

Proper Shipping Name	POTASSIUM HYDROXIDE SOLUTION
Class	8 Corrosive Substances
Subsidiary Risk(s)	No Data Available
UN Number	1814
Hazchem	2R
Pack Group	II
Special Provision	No Data Available

#### National Transport Commission (Australia)

Australian Code for the Transport of Dangerous Goods by Road & Rail (ADG Code)

Dangerous Goods Classification	Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road & Rail (ADG Code)
--------------------------------	---

### 15. REGULATORY INFORMATION

General Information	POTASSIUM HYDROXIDE
Poisons Schedule (Aust)	Schedule 6

#### Environmental Protection Authority (New Zealand)

Hazardous Substances and New Organisms Amendment Act 2015

Approval Code	HSR001574 (Reissued)
---------------	----------------------

#### National/Regional Inventories

Australia (AIC)	Listed
Canada (DSL)	Not Determined
Canada (NDSL)	Not Determined
China (IECSC)	Not Determined
Europe (EINECS)	215-181-3
Europe (REACH)	Not Determined
Japan (ENCS/METI)	Not Determined
Korea (KECI)	Not Determined



Malaysia (EHS Register)	Not Determined
New Zealand (NZIoC)	Listed
Philippines (PICCS)	Not Determined
Switzerland (Giftliste 1)	Not Determined
Switzerland (Inventory of Notified Substances)	Not Determined
Taiwan (NCSR)	Not Determined
USA (TSCA)	Listed

16. OTHER INFORMATION

Related Product Codes	CAPOLB1000, CAPOLB1001, CAPOLB1002, CAPOLB1100, CAPOLB1200, CAPOLB1244, CAPOLB1300, CAPOLB1400, CAPOLI1000, CAPOLI1001, CAPOLI1002, CAPOLI1003, CAPOLI1004, CAPOLI1005, CAPOLI1006, CAPOLI1007, CAPOLI1008, CAPOLI1009, CAPOLI1010, CAPOLI1100, CAPOLI1101, CAPOLI1200, CAPOLI1201, CAPOLI1202, CAPOLI1203, CAPOLI1300, CAPOLI1350, CAPOLI1351, CAPOLI1352, CAPOLI1400, CAPOLI1401, CAPOLI1500, CAPOLI1600, CAPOLI1800, CAPOLI2000, CAPOLI2100, CAPOLI2101, CAPOLI2150, CAPOLI2151, CAPOLI2152, CAPOLI2155, CAPOLI2200, CAPOLI2500, CAPOLI3000, CAPOLI3001, CAPOLI3010, CAPOLI3500, CAPOLI3600, CAPOLI3700, CAPOLI4000, CAPOLI8000, CAPOLI9000, CAPOLI9050, CAPOTA1721, CAPOTA1725, CAPOTA1801, CAPOTA1802, CAPOTA1803, CAPOTA1804, CAPOTA1805, CAPOTA1806, CAPOTA1807, CAPOTA1808, CAPOTA1809, CAPOTA1810, CAPOTA1811, CAPOTA1812, CAPOTA1820, CAPOTA1821, CAPOTA1822, CAPOTA1823, CAPOTA1825, CAPOTA1865, CAPOTA1866, CAPOTA1867, CAPOTA1868, CAPOTA1886, CAPOTA1887, CAPOTA1888, CAPOTA1889, CAPOTA1890, CAPOTA1891, CAPOTA1892, CAPOTA1893, CAPOTA1894, CAPOTA1895, CAPOTA1896, CAPOTA1897, CAPOTA1898, CAPOTA1899, CAPOTA1902, CAPOTA1903, CAPOTA1910, CAPOTA1915, CAPOTA1916, CAPOTA1940, CAPOTA1942, CAPOTA1945, CAPOTA4500, CAPOTA8888
Revision	3
Revision Date	22/08/2024
Reason for Issue	Updated SDS
Key/Legend	< Less Than > Greater Than <b>AICS</b> Australian Inventory of Chemical Substances <b>atm</b> Atmosphere <b>CAS</b> Chemical Abstracts Service (Registry Number) <b>cm²</b> Square Centimetres <b>CO2</b> Carbon Dioxide <b>COD</b> Chemical Oxygen Demand <b>deg C (°C)</b> Degrees Celcius <b>EPA (New Zealand)</b> Environmental Protection Authority of New Zealand <b>deg F (°F)</b> Degrees Farenheit <b>g</b> Grams <b>g/cm³</b> Grams per Cubic Centimetre <b>g/l</b> Grams per Litre <b>HSNO</b> Hazardous Substance and New Organism <b>IDLH</b> Immediately Dangerous to Life and Health <b>immiscible</b> Liquids are insoluable in each other. <b>inHg</b> Inch of Mercury <b>inH2O</b> Inch of Water <b>K</b> Kelvin <b>kg</b> Kilogram <b>kg/m³</b> Kilograms per Cubic Metre <b>lb</b> Pound <b>LC50</b> LC stands for lethal concentration. LC50 is the concentration of a material in air which causes the death of 50% (one half) of a group of test animals. The material is inhaled over a set period of time, usually 1 or 4 hours. <b>LD50</b> LD stands for Lethal Dose. LD50 is the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals. <b>ltr</b> or <b>L</b> Litre <b>m³</b> Cubic Metre <b>mbar</b> Millibar <b>mg</b> Milligram <b>mg/24H</b> Milligrams per 24 Hours <b>mg/kg</b> Milligrams per Kilogram

**mg/m<sup>3</sup>** Milligrams per Cubic Metre

**Misc** or **Miscible** Liquids form one homogeneous liquid phase regardless of the amount of either component present.

**mm** Millimetre

**mmH<sub>2</sub>O** Millimetres of Water

**mPa.s** Millipascals per Second

**N/A** Not Applicable

**NIOSH** National Institute for Occupational Safety and Health

**NOHSC** National Occupational Health and Safety Commission

**OECD** Organisation for Economic Co-operation and Development

**Oz** Ounce

**PEL** Permissible Exposure Limit

**Pa** Pascal

**ppb** Parts per Billion

**ppm** Parts per Million

**ppm/2h** Parts per Million per 2 Hours

**ppm/6h** Parts per Million per 6 Hours

**psi** Pounds per Square Inch

**R** Rankine

**RCP** Reciprocal Calculation Procedure

**STEL** Short Term Exposure Limit

**TLV** Threshold Limit Value

**tne** Tonne

**TWA** Time Weighted Average

**ug/24H** Micrograms per 24 Hours

**UN** United Nations

**wt** Weight